

Type	L (mm)	Gantry	T (mm)	Wt (kg/m)
27.1	2700	60 - 90	2115	234
27.2	2700	100 - 130	1915	234
29.1	2950	60 - 90	2365	262
29.2	2950	100 - 130	2165	262
32.1	3200	60 - 90	2615	290
32.2	3200	100 - 130	2415	290
34.1	3450	60 - 90	2865	318
34.2	3450	100 - 130	2665	318
37.1	3700	60 - 90	3115	346
37.2	3700	100 - 130	2915	346
39.1	3950	60 - 90	3365	374
39.2	3950	100 - 130	3165	374
42.1	4200	60 - 90	3615	402
42.2	4200	100 - 130	3415	402
46.1	4600	60 - 90	4015	402
46.2	4600	100 - 130	3815	402
52.1	5200	60 - 90	4615	514
52.2	5200	100 - 130	4415	514

**Note**

Gantry beam 2221 o/w

**Associated parts**

Cross arm for upright 2253

Cross arm for suspension 2311 o/w

Earth rope clamp 6211

Earth rope clamp 6219

**Fasteners**

Supplied complete with carrying angles and hook bolts.

**Resistance**

$F_{Rd}$  (kN) = 7,5

**Drawing number**

348.00116 -.00120, 348.00122 -.00125

**Ordering information**

Length 3,20 m, on J 60

2252.32.1 Upright on gantry beam

