

Type	L (mm)	Gantry	T (mm)	Wt (kg)
27.1	2700	60 - 90	2115	56.3
27.2	2700	100 - 130	1915	63.2
29.1	2950	60 - 90	2365	60.1
29.2	2950	100 - 130	2165	67.0
32.1	3200	60 - 90	2615	64.3
32.2	3200	100 - 130	2415	71.3
34.1	3450	60 - 90	2865	68.2
34.2	3450	100 - 130	2665	75.1
37.1	3700	60 - 90	3115	72.1
37.2	3700	100 - 130	2915	79.0
39.1	3950	60 - 90	3365	76.6
39.2	3950	100 - 130	3165	83.5
42.1	4200	60 - 90	3615	80.6
42.2	4200	100 - 130	3415	87.5
46.1	4600	60 - 90	4015	86.8
46.2	4600	100 - 130	3815	93.7
52.1	5200	60 - 90	4615	97.2
52.2	5200	100 - 130	4415	104.2

Note

Gantry beam 2221 onw

Associated parts

Cross arm for upright 2253

Cross arm for suspension 2311 onw

Earth rope clamp 6211

Earth rope clamp 6219

Fasteners

Supplied complete with carrying angles and hook bolts.

Resistance

F_{Rd} (kN) = 7,5

Drawing number

348.00116 -.00120, 348.00122 -.00125

Ordering information

Length 3,20 m, on J 60

2252.32.1 Upright on gantry beam

