

**Pole range**

Section HEB 200-260

Type	L (m)	HA (m)	Wt (kg)	F1 <sub>Rd</sub> (kN)	F2 <sub>Rd</sub> (kN)	F3 <sub>Rd</sub> (kN)
050	5.0	1.60	144	3.2	1.7	1.7
055	5.5	1.60	155	3.2	2.1	2.1
060	6.0	1.60	167	3.2	2.5	2.5
065	6.5	1.60	178	3.2	3.0	3.0
070	7.0	1.60	190	3.2	3.0	3.0
075	7.5	1.60	201	3.2	3.0	3.0
080	8.0	1.60	213	3.2	3.0	3.0
085	8.5	2.00	224	3.2	3.0	3.0
090	9.0	2.00	236	3.2	3.0	3.0
095	9.5	2.00	247	3.2	3.0	3.0
100	10.0	2.00	259	3.2	3.0	3.0

**Note**

Resistance

F1<sub>Rd</sub>, F2<sub>Rd</sub>, F3<sub>Rd</sub> see table

A separate calculation is required if the geometries and/or loads deviate from the tabled values

**Associated parts**

Clamp for suspension 5313

Drop bracket 2143

Cross arm for feeder 2351 o/w

Earth rope clamp for cantilever 6216

**Fasteners**

Supplied complete with U-bolts.

**Drawing number**

353.01079 - .01082

**Ordering information**

Length 8,5 m, on HEB 220

2113.1.85.22 Cantilever for 2 tracks

(type III / UNP 100)

