

**Mast range**

HEB profiles 160-240

Type	L (m)	L1 (mm)	H (m)	HA (mm)	Wt (kg)	F2 <sub>Rd</sub> (kN)
46.15	4.6	1200	1.5	1320	92	2.6
46.20	4.6	1200	2.0	1320	101	1.3
46.25	4.6	1200	2.5	1320	108	0.6
51.15	5.1	1224	1.5	1370	101	2.6
51.20	5.1	1224	2.0	1370	110	1.3
51.25	5.1	1224	2.5	1370	117	0.6
55.15	5.5	1200	1.5	1390	107	2.6
55.20	5.5	1200	2.0	1390	115	1.3
55.25	5.5	1200	2.5	1390	122	0.6
62.15	6.2	1224	1.5	1500	119	2.6
62.20	6.2	1224	2.0	1500	127	1.3
62.25	6.2	1224	2.5	1500	134	0.6

**Associated parts**

- Clamp for suspension 5311
- Bracket for steady arm Type 65 5413
- Cross arm for feeder 2351 onw
- Earth rope clamp for pull-off arm 6217

**Fasteners**

Supplied complete with U-bolts and long shank bolts.

Associated parts for wooden pole:

- Bracket for termination 3217
- Compression clamp 2194

**Resistance**

F1<sub>Rd</sub> (kN) = 3,0

**Drawing number**

351.00041 - .00043

**Ordering information**

Length 5,5 m, pull-off arm 2,0 m, on HEB 240

2114.55.20.24 Cantilever for 1 track with pull-off arm (type IV)

