

Type	L (m)	F <sub>Rd</sub> (kN)	Wt (kg)																											
050	5.00	195	211																											
055	5.50	195	233																											
060	6.00	195	250																											
065	6.50	195	265																											
070	7.00	195	281																											
075	7.50	195 </tr <tr> <td>080</td> <td>8.00</td> <td>182</td> <td>319</td> </tr> <tr> <td>085</td> <td>8.50</td> <td>161</td> <td>335</td> </tr> <tr> <td>090</td> <td>9.00</td> <td>142</td> <td>351</td> </tr> <tr> <td>095</td> <td>9.50</td> <td>125</td> <td>367</td> </tr> <tr> <td>100</td> <td>10.00</td> <td>111</td> <td>383</td> </tr> <tr> <td>105</td> <td>10.50</td> <td>95</td> <td>400</td> </tr> <tr> <td>110</td> <td>11.00</td> <td>82</td> <td>415</td> </tr>	080	8.00	182	319	085	8.50	161	335	090	9.00	142	351	095	9.50	125	367	100	10.00	111	383	105	10.50	95	400	110	11.00	82	415
080	8.00	182	319																											
085	8.50	161	335																											
090	9.00	142	351																											
095	9.50	125	367																											
100	10.00	111	383																											
105	10.50	95	400																											
110	11.00	82	415																											

**Note**

Length L = adjustable in 20mm increments (max. ±260)

Mast bracket 1343.1

Strut connection to foundation 1348.1

**Drawing number**

334.00223, .00223-1, .00223-2

**Ordering information**

Length 9.5 m

1341.2.095 Telescopic strut insulated

