

Mast range

HEB profiles 160-260
Lengths 5,00 - 16,00 m

| Type | HEB (mm) | Wt (kg/m) | M (mm) | d (mm) | t (mm) |
|------|-------------|--------------|-----------|-----------|-----------|
| 16 | 160 | 42.6 | 30 | 39 | 35 |
| 18 | 180 | 51.2 | 30 | 39 | 35 |
| 20 | 200 | 61.3 | 30 | 39 | 35 |
| 22 | 220 | 71.5 | 30 | 39 | 35 |
| 24 | 240 | 83.2 | 36 | 45 | 40 |
| 26 | 260 | 93.0 | 36 | 45 | 40 |

Note

Available in 0,50 m steps.
When ordering state length L.
Max. Note load for transport by helicopter.
x = bonding point for earthing 2 x M12

Additional weight for base plate:

HEB 160-220 50 kg
HEB 240-260 60 kg

Associated parts

Mast extension 1231 onw
Foundation material 1111 onw
Insulating set 6311

Fasteners

Connection on
bridge/wall 1414 onw

Drawing number

328.00240, .00241, .00267, .00270,
.00272, .00274

Ordering information

HEB 240, Length 12,00 m
1212.24.120 Wide-flanged mast with
base plate

