

**Material**

Insulation Synthetic material

Fittings Fe stainless

Type	Used for
1	with clamp for stitch wire for cable $\varnothing$ 6 mm
2.1	with pulley for stitch wire for cable $\varnothing$ 6 mm
2.2	with pulley for kevlar rope $\varnothing$ 10 mm
3	with hinged rope clamp
4	with contact wire swivel clip, groove type
5	for steady arm tube
6	with eyebolt for hinged suspension, suspension, delta cable
7	with feeder suspension clamp
8	with hold-down clamp, spring-loaded and movable

**Note**

When ordering state tube diameter.

Standard diameters 70 mm

Other diameters on request

**Associated parts**

Hinged rope clamp 5351

Contact wire swivel clip 5557

Steady arm tube

with eye end fitting 5523

Delta cable 5565 onw

Feeder suspension clamp 5353

Flat laying steady arm 5571

**Fasteners**

Supplied complete with U-Bolts.

**Resistance**

valid for all types, exclusive for type 8

$F_{1Rd}$  (kN) = 2

$F_{2Rd}$  (kN) = 4

**Drawing number**

353.00351 - .00351-7

**Ordering information**

On tube  $\varnothing$  70 mm, with contact wire swivel clip,

groove type

2187.70.4 Insulated suspension for tube 70

mm, 1.5 kV

