Material
Insulation Synthetic material
Fittings Fe stainless

Type	Used for
1	with clamp for stitch wire for cable ø 6 mm
2.1	with pulley for stitch wire for cable ø 6 mm
2.2	with pulley for kevlar rope ø 10 mm
3	with hinged rope clamp
4	with contact wire swivel clip, groove type
5	for steady arm tube
6	with eyebolt for hinged suspension, suspension, delta cable
7	with feeder suspension clamp
8	with hold-down clamp, spring-loaded and movable

Note
When ordering state tube diameter.
Standard diameters 70 mm
Other diamteters on request

Associated parts
Hinged rope clamp 5351
Contact wire swivel clip 5557
Steady arm tube
with eye end fitting 5523
Delta cable 5565 onw
Feeder suspension clamp 5353
Flat laying steady arm 5571


Fasteners
Supplied complete with U-Bolts.

Resistance
valid for all types, exclusive fot type 8
$F1_{Rd}$ (kN) = 2
$F2_{Rd}$ (kN) = 4


Drawing number
353.00351 - .00351-7

Ordering information
On tube ø 70 mm, with contact wire swivel clip, groove type
2187.70.4 Insulated suspension for tube 70 mm, 1.5 kV


2187.xx.1




2187.xx.2.1/2187.xx.2.2




2187.xx.3




2187.xx.4




2187.xx.5



2187.xx.6



2187.xx.7



2187.xx.8

