

**Material**

Insulation Synthetic material

Fittings Fe stainless

**Type Used for**

Type	Used for
1	with delta cable clamp for cable $\varnothing$ 6 mm
2.1	with pulley for steel cable $\varnothing$ 6 mm
2.2	with pulley for Kevlar rope $\varnothing$ 10 mm
3	with hinged rope clamp
4	with contact wire swivel clip, groove type
5	for steady arm tube
6	with eyebolt for hinged suspension, suspension, delta cable
7	with feeder suspension clamp
8	with hold-down device, spring-loaded and movable

**Note**on cross span  $\varnothing$  4,5 - 9 mm / 35 - 50 mm<sup>2</sup>**Associated parts**

Hinged rope clamp 5351

Contact wire swivel clip 5557

Steady arm tube

with eye end fitting 5523

Delta cable 5565 onw

Feeder suspension clamp 5353

Flat laying steady arm 5571

**Resistance**

valid for all types, exclusive for type 8

 $F_{1Rd}$  (kN) = 1 $F_{2Rd}$  (kN) = 4**Drawing number**

353.00352 - .00352-6, 451.00360

**Ordering information**with pulley for Kevlar rope  $\varnothing$  10 mm

2189.2.2 Insulated suspension for cross span, long, 1.5

kV

