

Material

Insulation Synthetic material

Fittings Fe stainless

| Type | Used for |
|------|---|
| 1 | with delta cable clamp for cable \varnothing 6 mm |
| 2.1 | with pulley for steel cable \varnothing 6 mm |
| 2.2 | with pulley for Kevlar rope \varnothing 10 mm |
| 3 | with hinged rope clamp |
| 4 | with contact wire swivel clip, groove type |
| 5 | for steady arm tube |
| 6 | with eyebolt for hinged suspension, suspension, delta cable |
| 7 | with feeder suspension clamp |
| 8 | with hold-down device, spring-loaded and movable |

Noteon cross span \varnothing 4,5 - 9 mm / 35 - 50 mm²**Associated parts**

Hinged rope clamp 5351

Contact wire swivel clip 5557

Steady arm tube

with eye end fitting 5523

Delta cable 5565 onw

Feeder suspension clamp 5353

Flat laying steady arm 5571

Resistance

valid for all types, exclusive for type 8

 F_{1Rd} (kN) = 1 F_{2Rd} (kN) = 4**Drawing number**

353.00352 - .00352-6, 451.00360

Ordering informationwith pulley for Kevlar rope \varnothing 10 mm

2189.2.2 Insulated suspension for cross span, long, 1.5

kV

